



Altius Axia Classic Emulsion Interior / Exterior Emulsion Paint

Product Description:

Altius Axia Classic Emulsion is a superior quality, emulsion paint based on high quality acrylic co-polymers. It provides a smooth and good quality finish suitable for application on interior or exterior surface. It provides anti-fungal and anti-bacterial properties from the additives in it.

Advantages At A Glance

- High durability.
- High quality professional finish.
- Excellent coverage.
- Weather resistant (for external surface).

Preparation Of Surface

Remove dust, dirt, oil patches, protrusions, ridges and foreign matter from the areas to be coated. Ensure the substrate has sufficient strength to receive the paint. Any defects in the substrate like surface undulations, cracks, pin holes etc., should be rectified and covered before painting. Before applying to old painted surfaces, ensure that the surface is washed with water/soda solution. Rinse and allow the surface to dry before application.

Priming

Prime the surface using Altius PVA Primer.

Method Of Application

Apply the paint by brush, roller or spray upto 2 coats. The application operation should be continuous in order to avoid dry edges. Leave 2 to 4 hours between coats. Clean tools and equipment with water after use.

Health & Safety

Keep away from contact of eyes and skin by wearing overalls, safety boots, goggles, gloves and mask. For further information, please refer the Material Safety Data Sheet.



Gloves



Boots



Gloves



Boots

Packing & Storage

Product is supplied in 18 L & 3.5 L plastic pail. Store in a clean dry area, protected from direct sunlight and extreme temperatures (both heat and cold). They have a shelf life of up to 12 months. The oldest material should be used first.

Altius Axia Classic Emulsion

Technical Data

Product	Superior quality interior/ exterior emulsion paint
Binder	Acrylic co-polymer
Colour	Available in a range of attractive shades
Finish	Matt / Silk / Gloss
Drying time	1 hour touch dry, 2-4 hours between coats
Application	Brush, roller or spray
Dilution	If necessary, with water
Storage	12 months in original, unopened condition
Package	18 L & 3.5 L plastic pail

Disclaimer:

The information in this document is given to the best of Altius Industries knowledge, based on laboratory testing and practical experience and is intended to provide general information on the product and their method of application. All Altius products are used under conditions beyond Altius control so we cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. The prospective user is recommended to determine the suitability of products before adopting them on a commercial scale. Altius reserves the right to change the given data without further notice. Users should always consult Altius technical team for specific guidance on the general suitability of this product for their needs and specific application practices.

For Sales & Technical Support:

✉ info@altius-me.com ✉ sales@altius.llc

ALTIUS INDUSTRIES LLC

P.O.BOX : 16135, United Arab Emirates



