

Altius Axia Emulsion Interior Emulsion Paint

PRODUCT DESCRIPTION:

Altius Axia Emulsion is a good quality, economical emulsion paint based on acrylic polymers. It provides a smooth and good quality finish suitable for application on interior surface only. It provides anti-fungal and anti-bacterial properties from the additives in it.

ADVANTAGES AT A GLANCE

- Economical.
- Good quality finish.
- Good brushability.

AREAS OF USAGE

Altius Axia Emulsion is suitable for smooth decorative finish and protection of both old and new interior surface like concrete, plasterboards, gypsum boards etc.

PREPARATION OF SURFACE

Remove dust, dirt, oil patches, protrusions, ridges and foreign matter from the areas to be coated. Ensure the substrate has sufficient strength to receive the paint. Any defects in the substrate like surface undulations, cracks, pin holes etc., should be rectified and covered before painting. Before applying to old painted surfaces, ensure that the surface is washed with water/soda solution. Rinse and allow the surface to dry before application.

PRIMING

Prime the surface using Altius PVA Primer.

METHOD OF APPLICATION

Apply the paint by brush, roller or spray upto 2 coats. The application operation should be continuous in order to avoid dry edges. Leave 2 to 4 hours between coats. Clean tools and equipment with water after use.

HEALTH & SAFETY

Keep away from contact of eyes and skin by wearing overalls, safety boots, goggles, gloves and mask. For further information, please refer the Material Safety Data Sheet.

PACKING & STORAGE

Product is supplied in 18 L & 3.5 L plastic pail. Store in a clean dry area, protected from direct sunlight and extreme temperatures (both heat and cold). They have a shelf life of up to 12 months. The oldest material should be used first.

Altius Axia Emulsion

TECHNICAL DATA

Product	High quality interior emulsion paint
Binder	Acrylic polymer
Colour	Available in a range of attractive shades
Finish	Matt / Semi Matt
Drying time	30 mins touch dry, 2-4 hours between coats
Application	Brush, roller or spray
Dilution	If necessary, with water
Storage	12 months in original, unopened condition
Package	18L & 3.5L plastic pail

DISCLAIMER

The information in this document is given to the best of Altius Industries knowledge, based on laboratory testing and practical experience and is intended to provide general information on the product and their method of application. All Altius products are used under conditions beyond Altius control so we cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. The prospective user is recommended to determine the suitability of products before adopting them on a commercial scale. Altius reserves the right to change the given data without further notice. Users should always consult Altius technical team for specific guidance on the general suitability of this product for their needs and specific application practices.

Contact information

For Sales & Technical Support :
E: info@altius-me.com
E: sales@altius-me.com

Address

ALTIUS INDUSTRIES LLC
P.O.BOX : 16135
United Arab Emirates

www.altius-me.com

