

Technical Data Sheet

Altius Tex

PRODUCT DESCRIPTION:

Altius Tex is a highly flexible water based acrylic textured coating. They are weather resistant and used to decorate and protect all kinds of surfaces like concrete, stucco, plasters and EIFS. They have excellent dirt pickup resistant properties, keeps surfaces cleaner and provides high surface durability.

ADVANTAGES AT A GLANCE

- High weather resistance.
- Excellent adhesion.
- High Coverage.

AREAS OF USAGE

Recommended for exterior surface of buildings where textured finish is required.

PREPARATION OF SURFACE

Ensure that the surface is level and all dust, dirt and foreign matters are brushed and scraped away. Also ensure the surface is solid and free from salts, oil grease and ridges. Before applying to old painted surfaces, ensure that the surface is washed with water/soda solution. Rinse and allow the surface to dry before application.

PRIMING

Prime the surface using Altius PVA Primer.

METHOD OF APPLICATION

Mix the material well before application. Use a steel trowel to lay on the material on to the primed surface and finished using a wet plastic trowel. Clean tools and equipment with water after use.

HEALTH & SAFETY

Keep away from contact of eyes and skin by wearing overalls, safety boots, goggles, gloves and mask. For further information, please refer the Material Safety Data Sheet.

PACKING & STORAGE

Product is supplied in 18L plastic pail. Store in a clean dry area, protected from direct sunlight and extreme temperatures (both heat and cold). They have a shelf life of up to 12 months. The oldest material should be used first.



Altius Tex

TECHNICAL DATA

Product	Acrylic based textured coating
Binder	Acrylic binder
Fillers	Mineral fillers
Colour	White, other colours on request
Toxicity	Non-toxic Non-toxic
Application	Trowel
Available grain size	0-1mm, 0-2mm, 0-3mm
Dilution	If necessary, with water
Storage	12 months in original, unopened condition
Package	18 L plastic pail

DISCLAIMER

The information in this document is given to the best of Altius Industries knowledge, based on laboratory testing and practical experience and is intended to provide general information on the product and their method of application. All Altius products are used under conditions beyond Altius control so we cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. The prospective user is recommended to determine the suitability of products before adopting them on a commercial scale. Altius reserves the right to change the given data without further notice. Users should always consult Altius technical team for specific quidance on the general suitability of this product for their needs and specific application practices.

Contact information

For Sales & Technical Support: E: info@altius-me.com

E: sales@altius-me.com

Address

ALTIUS INDUSTRIES LLC

P.O.BOX: 16135 United Arab Emirates

www.altius-me.com







