

## Technical Data Sheet

# **Altius Duct Coat**



#### **PRODUCT DESCRIPTION:**

Altius Duct Coat is a lagging cloth adhesive and coating for use with insulation on air conditioning ducts. Altius Duct Coat is a acrylic based washable and abrasion resistant and has a neat white finish.

#### **ADVANTAGES AT A GLANCE**

- Water Resistant.
- Superior Flexibility.
- Non yellowing.
- Dirt & Mold Resistant.

#### **AREAS OF USAGE**

Used as both adhesive and coating for lagging cloth for canvas and fiberglass.

#### **PREPARATION OF SURFACE**

Ensure dust, dirt and foreign matter are removed from the surface.

#### **METHOD OF APPLICATION**

Apply a layer of Altius Duct Coat on the insulation surface by brush and place the lagging cloth on the wet surface. Immediately apply another layer of Altius Duct Coat as a final coat and allow it to dry. Clean all tools and equipment with water after use.

#### **HEALTH & SAFETY**

Keep away from contact of eyes and skin by wearing overalls, safety boots, goggles, gloves and mask. For further information, please refer the Material Safety Data Sheet.

#### **PACKAGING & STORAGE**

Product is supplied in 20 Kg plastic pail. Store in a clean dry area, protected from direct sunlight and extreme temperatures (both heat and cold). They have a shelf life of up to 12 months. The oldest material should be used first.



#### **TECHNICAL DATA**

Product	Lagging cloth adhesive and coat
Binder	Acrylic binder
Colour	Off white
Specific Gravity	1.3
pН	8-8.5
Consumption	1.2 Kg/m <sup>2</sup> /mm
Storage	12 months in original, unopened condition
Package	20 Kg plastic pail

#### DISCLAIMER

The information in this document is given to the best of Altius Industries knowledge, based on laboratory testing and practical experience and is intended to provide general information on the product and their method of application. All Altius products are used under conditions beyond Altius control so we cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. The prospective user is recommended to determine the suitability of products before adopting them on a commercial scale. Altius reserves the right to change the given data without further notice. Users should always consult Altius technical team for specific guidance on the general suitability of this product for their needs and specific application practices.

Contact information For Sales & Technical Support : E: info@altius-me.com E: sales@altius-me.com

Address ALTIUS INDUSTRIES LLC P.O.BOX : 16135 United Arab Emirates

### www.altius-me.com



