

## Altius Stucco Putty



### PRODUCT DESCRIPTION:

Altius Stucco Putty is an acrylic co-polymer ready to use filler, used on most building surfaces. Altius Stucco Putty is used to repair and touch up interior surfaces, both old and new, and provides a high quality even surface prior to painting. It is also used to fill joints and hairline cracks. When dry, Altius Stucco Putty bonds extremely well to most surfaces like cementitious materials, gypsum boards, wood, galvanized steel lath and all other common building surfaces.

### ADVANTAGES AT A GLANCE

- High plastic properties
- No flaking.
- Permanent and retains adhesion.

### AREAS OF USAGE

As a thin coat filler where it is not possible to use spray plaster. Patching of hairline cracks in walls, ceilings, repair to damaged plaster work / paint work, filling of defects / nails / holes in woodwork, making good around door architraves, and along the top of skirting etc.

### PREPARATION OF SURFACE

Repair irregular and loose areas and remove protrusions. Dust, dirt and foreign matter should be removed by brushing and vacuuming the surface. All oil and greasy residues such as ridges and form oil

and release agents should be cleaned out. Surfaces affected by rising damp should be treated with a damp proofing system prior to application of filler. If damp is a constant danger, then the use of Altius Acrylic Filler is recommended.

### PRIMING

If the surface is porous, it is recommended to use Altius Primer to have a stable surface prior to application of Altius Roof Coat.

### APPLICATION

Apply the filler in a thin even layer using a spatula; if the area under repair requires a thick coat then apply several thin layers, allowing each layer to dry before adding the next. Lightly sandpaper over the dry final surface before painting preferably within 24 hours of application.

### HEALTH & SAFETY

Keep away from contact of eyes and skin by wearing overalls, safety boots, goggles, gloves and mask. For further information, please refer the Material Safety Data Sheet.

### PACKAGING & STORAGE

Altius Stucco Putty is supplied in 5 Kg and 20 Kg plastic pails. Store in a clean dry area, protected from direct sunlight and extreme temperatures (both heat and cold). They have a shelf life of up to 12 months. The oldest material should be used first.

## TECHNICAL DATA

Product	Ready-mixed quick drying filler of fine inert extenders
Filler	Precisely graded marble
Binder	Acrylic co-polymer
Dilution	Water if required
Density	1.75
Colour	White
Shrinkage	Negligible
Application	By Spatula
Material Consumption	6 - 8 sq. mt / Kg
Storage	12 months in original, unopened packs
Packaging	5 Kg and 20 Kg plastic pail

## DISCLAIMER

The information in this document is given to the best of Altius Industries knowledge, based on laboratory testing and practical experience and is intended to provide general information on the product and their method of application. All Altius products are used under conditions beyond Altius control so we cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. The prospective user is recommended to determine the suitability of products before adopting them on a commercial scale. Altius reserves the right to change the given data without further notice. Users should always consult Altius technical team for specific guidance on the general suitability of this product for their needs and specific application practices.

### Contact information

For Sales & Technical Support :

E: [info@altius-me.com](mailto:info@altius-me.com)

E: [sales@altius-me.com](mailto:sales@altius-me.com)

### Address

**ALTIUS INDUSTRIES LLC**

P.O.BOX : 16135

United Arab Emirates

[www.altius-me.com](http://www.altius-me.com)

